

5 MODELS HUNDREDS OF OPTIONS

Artico manufactures three different lifts for the home market: The Aritco 4000, Aritco HomeLift Access and Aritco HomeLift. And three models for public & commercial market: The Aritco PublicLift Access, Aritco 9000. Find out which model and size is best for you.





Aritco HomeLift

Key features

Aritco HomeLift comes with luxury design features like the DesignWall, a backlit wall with selected art from prominent Scandinavian designers, and DesignLight, with state-of-the-art lighting that you can control via the SmartLift app. The lift is operated via a unique solution: a steering wheel called the SmartControl. The lift is equipped with our SmartSafety system, with safety features that anticipate situations and prevent accidents.

Sizes



MODEL	CARRIER SIZE	EXTERIOR DIMENSIONS	RATED LOAD
S5	600 x 830 mm	966 x 880 mm	250 kg / 2 persons
S8	1000 x 830 mm	1366 x 880 mm	250 kg / 3 persons
S9	1100 x 830 mm	1466 x 880 mm	250 kg / 3 persons
S12	1000 x 1200 mm	1366 x 1250 mm	400 kg / 5 persons
S15	1100 x 1400 mm	1466 x 1450 mm	400 kg / 5 persons

DesignWall



















Lift color



Glass STANDARD Clear glass

OPTIONAL Tinted glass



Floor













Intended use

Installations in private homes Indoor installation environments

Technical compliance

European Machine Directive 2006/42/EC European Standard EN 81-41

Drive system

Patented screw-and-nut system

Rated speed

Max 0.15 m/s inside Europe Max 0.30 m/s outside Europe

Emergency lowering

Battery-powered

Travel height

250 - 15 000 mm

Top height

Min. 2 225 mm to 4 000 mm

Number of floors

2 to 6 floors

Installation

Recessed installation 37 mm below floor level Installed directly on the floor with a ramp

Operation

Hold to run (press and hold)

One-touch operation (press one time) for installations outside Europe

Power supply

230 V 1-phase 400 V 3-phase

Warranty

Aritco HomeLift comes with a 60-month warranty
The screw-and-nut assembly has a 10-year warranty




Aritco HomeLift Access

Alternative model **Outdoor version**

Key features

Aritco HomeLift Access comes with many customization options. You can personalize your lift by choosing from more than 200 different colors, two different glass types and eight different floorings. The lift is very practical and smart and increases your home's accessibility for everyone. It comes in several different sizes. The larger models accomodate a stroller or wheelchair. The lift is equipped with our SmartSafety system, with safety features that anticipate situations and prevent accidents.

Sizes



MODEL	CARRIER SIZE	EXTERIOR DIMENSIONS	RATED LOAD
1	900 x 1040 mm	1300 x 1160 mm	250 kg / 2 persons
2	900 x 1280 mm	1300 x 1400 mm	410 kg / 5 persons
3	900 x 1480 mm	1300 x 1600 mm	410 kg / 5 persons
4	1000 x 1280 mm	1400 x 1400 mm	410 kg / 5 persons
5	1000 x 1480 mm	1400 x 1600 mm	410 kg / 5 persons
6	1100 x 1480 mm	1500 x 1600 mm	410 kg / 5 persons
7	1000 x 1980 mm	1400 x 2100 mm	500 kg / 6 persons
8	1100 x 1580 mm	1500 x 1700 mm	500 kg / 6 persons

Can be painted in any RAL color Lift color from the RAL K7 classic chart (Except for pearl and fluorescent colours)



Glass	STANDARD
Glass	Clear glass







Floor	Dark Gran	Spht Clay	Solvery Vinst	Run de l'Aropean de	Ages of	A Stream	Pain Sand	Solow Spino
	ark Gla	9ht Gr	Oiled	opean	Ses oak	on Flo	on Sisa.	80101

	ank Green Ones of Open Por On Por On Start Solor			
Intended use	Installation in private homes Indoor and outdoor installation environments			
Technical compliance	European Machine Directive 2006/42/EC European Standard EN 81-41			
Drive system	Patented screw-and-nut system			
Rated speed	Max 0.15 m/s inside Europe Max 0.25 m/s outside Europe			
Emergency lowering	Battery-powered			
Travel height	250 – 13 000 mm			

Top height	Min. 2 240 mm	
Number of floors	2 to 6 floors	

Installation	Recessed installation 50 mm below floor level
Installation	Installed directly on floor with 50 mm ramp

Operation	Hold to run (press and hold) One-touch operation (press one time) for installations outside Europe
	, , , , , , , , , , , , , , , , , , , ,

Power supply	230 V 1-phase 400 V 3-phase	
Warranty	Aritco HomeLift Access comes with a 60-month warranty The screw-and-nut assembly has a 10-year warranty	

Alternative model	Aritco HomeLift Access OUTDOOR version is designed for outdoor use. All outdoor lifts are delivered with corrosion class C5 guides to avoid corrosion. For more information please visit aritco.com

The screw-and-nut assembly has a 10-year warranty



Aritco 4000

Key features

Aritco 4000 comes with several customization options to personalize your lift. You can choose between more than 200 different colors, two different glass types and eight different floorings. The lift is also very compact and space-efficient, which makes it possible to install the lift in almost any home, even where space is limited. The lift is equipped with our SmartSafety system, with safety features that anticipate situations and prevent accidents.

Sizes



MODEL	CARRIER SIZE	EXTERIOR DIMENSIONS	RATED LOAD
1	580 x 805 mm	840 x 880 mm	250 kg / 2 persons
2	880 x 805 mm	1140 x 880 mm	250 kg / 2 persons
3	1080 x 805 mm	1340 x 930 mm	250 kg / 2 persons

Lift color

Can be painted in any RAL color from the RAL K7 classic chart (Except for pearl and fluorescent colors)



Glass

STANDARD Clear glass



OPTIONAL Tinted



Floor
9 different floorings.















Intended use

Installation in private homes Indoor installation environments

Technical compliance

European Machine Directive 2006/42/EC European Standard EN 81-41

Drive system

Patented screw-and-nut system

Rated speed

Max 0.15 m/s

Emergency lowering

Battery-powered

Travel height

250 – 13 000 mm

Top height

Min. 2 300 mm

Number of floors

2 to 6 floors

Installation

Recessed installation 50 mm below floor level Installed directly on floor with 50 mm ramp

Operation

Hold to run (press and hold)

One-touch operation (press one time) for installations outside Europe

Power supply

230 V 1-phase

Warranty

Aritco 4000 comes with a 60-month warranty
The screw-and-nut assembly has a 10-year warranty

Aritco Public lift Access is designed to provide reliable

Aritco PublicLift Access is designed to provide reliable and safe access for everyone in public and commercial buildings. Practical and smart with sizes or all reeds. With customization possibilities, such as glass ralls, a range of various colours and different material


Aritco PublicLift Access

Alternative models
OUTDOOR version
GOODS version

Key feat ures

Aritco PublicLift Access comes with customization possibilities. When it comes to design and possibility to customize the lift, you can choose from more than 200 different colours, 2 different glass types and 8 different floors. The lift is very practical and smart and gives everyone access to different floors in public & commercial buildings. It comes in several different sizes, and on the larger ones you can fit a stroller or a wheelchair. It's reliable and has a robust design that can handle tough public & commercial environments. The lift is equipped with our SmartSafety system, with safety features, to meet all situations that can occur in public & commercial spaces, as well as to prevent accidents.

Cabin sizes



MODEL	CARRIER SIZE	EXTERIOR DIMENSIONS	RATED LOAD	WHEELCHAIR
1	900 x 1040 mm	1300 x 1160 mm	250 kg / 2 persons	-
2	900 x 1280 mm	1300 x 1400 mm	410 kg / 5 persons	Lone user or type A
3	900 x 1480 mm	1300 x 1600 mm	410, 500 kg / 5, 6 pers.	A or B with attendent
4	1000 x 1280 mm	1400 x 1400 mm	410 kg / 5 persons	Lone user or type A
5	1000 x 1480 mm	1400 x 1600 mm	410, 500 kg / 5, 6 pers.	A or B with attendent
6	1100 x 1480 mm	1500 x 1600 mm	410, 500 kg / 5, 6 pers.	A or B with attendent, adjacent entry
7	1000 x 1980 mm	1400 x 2100 mm	500 kg / 6 persons	A or B with attendent
8	1100 x 1580 mm	1500 x 1700 mm	500 kg / 6 persons	A or B with attendent, adjacent entry

National guidelines may apply. Wheelchair Type A and B according to EN 12183/EN 12184.

Lift color

Can be painted in any RAL color from the RAL K7 classic chart (Except for pearl and fluorescent colours)



Glass

4 different glass types to choose from.

STANDARD Clear glass



OPTIONAL Tinted glass



Floor

9 different floorings.















Installation environment:

Indoor

Type of lift

Platform lift intended for installation in public and commercial environments.

Drive system

Patented screw-and-nut system

Motor

2.2 kW motor

Rated speed

Max 0,15 m/s inside Europe Max 0.25 m/s outside Europe

Technical compliance

European Machine directive 2006/42/EC European standard EN 81-41

Emergency lowering

Battery-powered.

Travel height

250 – 13 000 mm

Top height

Min. 2 240

Number of floors

2 to 6 floors

Installation

Recessed installation 50 mm below floor Installed directly on the floor with 50 mm ramp

Operation

Hold to run – press and hold

For installations outside Europe – One touch operation (press one time)

Power supply

230 V 1-phase 400 V 3-phase

Warranty

Aritco PublicLift Access comes with a 60-month warranty The screw-and-nut assembly has a 10-year warranty

Alternative model

Aritco PublicLift Access GOODS version is a version of the Aritco PublicLift Access lift that is intended for both persons and goods.

Aritco PublicLift Access OUTDOOR version is designed for outdoor use. All outdoor lifts are delivered with corrosion class C5 guides to avoid corrosion.

For more information please visit aritco.com



ARITCO 9000






Key feat ures


Aritco 9000 comes with customization possibilities. When it comes to design and possibility to customize the lift, you can choose from more than 200 different colours, 2 different glass types and 7 different floors. The lift is very practical and smart and gives everyone access to different floors in public & commercial buildings. It comes in two different sizes, in which you can fit a stroller or a wheelchair. It's reliable and has a robust design that can handle tough public & commercial environments. The lift is equipped with our SmartSafety system, with safety features, to meet all situations that can occur in public & commercial spaces, as well as to prevent accidents.

Cabin sizes

Size: 1000 x 1400 mm Rated load: 400 kg / 5 pers. Wheelchair: A or B with attendent



Size: 1100 x 1400 mm Rated load: 400 kg / 5 pers. Wheelchair: A or B with attendent, adjacent entry



National guidelines may apply. Wheelchair Type A and B according to EN 12183/EN 12184

Lift color

Can be painted in any RAL colour from the Chart K7 classic chart (except for pearl and fluorescent colours)



Cabin color 22 different wall- and ceiling laminates to choose from.



















Glass

4 different glass types to choose from.











Floor

Motor

9 different floorings to choose from.













Installation environment:

Indoor

Type of lift

Platform lift intended for installation in public and commercial environments

Drive system

3 kW motor

Rated speed

Max 0.15 m/s inside Europe

Technical compliance

European Machine directive 2006/42/EC

Patented screw-and-nut system

Emergency lowering

Battery-powered

Travel height

2 150¹⁾ – 13 000 mm ¹⁾For opposite entry. 2300 mm when doors on same side

Top height

Min. 2 400

Number of floors

2 to 6 floors

Installation

Recessed installation 75 mm below floor Installed directly on the floor with ramp

Operation

Control from carrier control panel. - Press one time to operate lift

Power supply

400 V 3-phase

Warranty

Aritco 9000 comes with a 60 month warranty The screw and nut assembly has a 10 year warranty



Find your closest reseller at www.aritco.com Press & Social Media @aritco









